



# CRYSTORAMA


LIGHTING THE WAY FOR SIXTY YEARS

ASSEMBLY INSTRUCTION MODEL# ROY-802-BK

The fixture can be mounted both downwards and upwards




FRONT VIEW



SIDE VIEW

3 3/8" [85]



All electrical components must be installed by a licensed electrician in accordance with the National Electric Code and the appropriate local electrical codes.



You will need 2- Cand. Bulb  
40 Watts Recommended 60 Watts Max.  
USE LED BULBS FOR EXTENDED USE  
THE FIXTURE IS DAMP RATED

## How to install

1. Install the mounting plate to the outlet box using two outlet box screws.
2. Install backplate onto the mounting plate, and secure with two ball nuts
3. Install the bulb(not included) into the socket.
4. Please remove the black rubber pad on the four corners of the frame before proceeding with installation of the glass panel. Place the glass panel into the metal frame and secure with the clips.
5. Place the metal frame over the backplate and secure with the screws.

# CRYSTORAMA

LIGHTING THE WAY FOR SIXTY YEARS

ASSEMBLY INSTRUCTION MODEL# ROY-802-BK

## Part Number

### Part Numbers

- A. (1)-Mounting hardware
- B. (1)-Backplate W5-3/8"xH17-1/2"xE5/8"(XSU802BKBKP5.375IN)
- C. (4)-Screw
- D. (2)-Ball nut(XSU800BKBANUT)
- E. (1)-Glass Panel W6-5/8"xH17-1/2"xE3"( XSU802GLA6.625IN)
- F. (1)-Metal Frame W6-3/4"xH17-3/4"xE3-1/4"

