


The slim Allasio with 4 3/4" height is ideal where under-cabinet space is limited, plus the contemporary styling and gleaming colors will compliment other appliances and most cabinetry. Allasio features a 3-speed, 300 CFM internal blower, which provides sufficient ventilating power for most kitchens. The attractive, backlit push button controls illuminate an elegant blue glow when activated and allows the user to manage blower speeds and dual LED lamps.

Dishwasher-safe anodized aluminum mesh filters are easy to clean and a snap to remove and replace. Available in 30" or 36" widths, Allasio is designed for standard ducted installation, and can be installed as a recirculating system, using the Recirculating Kit.





	EAL330S1	EAL336S1
Α	30" (76.2 cm)	36" (91.4 cm)
В	20" (50.8 cm)	
С	4%" (12 cm)	
D	2¾" (5.7 cm)	
Е	3¼" x 10" (8.3 x 25.4 cm)	
F	5‰" (13 cm)	





SPECIFICATIONS





	30" UNIT	36" UNIT	
Model:	EAL330\$1	EAL336S1	
Dimensions:	30" W x 20" D x 4 3/4" H	36" W x 20" D x 4 3/4" H	
Blower Type(internal):	300 CFM (3 -speed)		
Blower Performance:			
Speed 1	120 CFM		
Speed 2	210 CFM		
Speed 3	300 CFM		
Noise (sones): Woking Speed	Min: 1.5, Max: 5.9		
Finish:	Stainless Steel		
Controls:	Hidden electronic touch controls		
Illumination: (replaceable lamps 1 intensity)	2 LED, 2.5 Watts		
Filter Type:	Dishwasher-Safe, Anodized Aluminum Mesh Filter		
Aluminum Mesh Filters:	1	2	
Duct Transition:	6" Round with Back Draft Damper (top only)		
Installation Type:	Ducted (Recirculating Kit sold separately)		
Electrical:	120V - 60 Hz 289 Watts at 2.43 Amps		
KITS:			
Recirculating Kit			
with 2 carbon filters:	КІТ02178	KIT02179	
Non return valve/back-	NITO	7702	
draft damper 7" round:		2/25	
CONSUMABLE PARTS:			
Grease Filter (1):	GF04BA	GF04BB	
Carbon Filter (1):	TM01FA	TM01FB	
Replacement Light Bulb (1):	LMP0117673		

*Consumable parts are sold in units of one (1). Order accordingly

PLUS FEATURES



