
# **ELECTRIC MIRROR®**



# PRODUCT DESCRIPTION

The Aria™ offers a delicate dichotomy of design for any project requiring a unique new look: the romantic curves of rounded corners combined with the exacting look of a symmetrical inset border of light.

#### **SPECIFICATION STATEMENT**

Solution shall consist of a radius-corner lighted mirror with forward-facing task lighting and corrosion-resistant glass. Mirror shall have uniform light output in frosted areas, using-replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in USA and have a 7-year limited warranty.

#### THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

# **FEATURES AND BENEFITS**

- Copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- Title 24 compliance available
- 7-year limited warranty
- Covered by one or more patents
- Proudly made in the USA

#### **AVAILABLE OPTIONS**

• Forward-phase dimming<sup>1</sup>

#### LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- Replaceable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin
- 604 lumens per foot
- Calculated L<sub>70</sub> 124,000-hour LED lifespan
- Maximum 100 lumens per watt efficacy

# **SAFETY SPECIFICATIONS**

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror



<sup>&</sup>lt;sup>1</sup>Minimum order quantity required.

# **INSTALLATION SPECIFICATIONS**

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Fixture should be controlled by an on/off switch
- · Installation wiring may be different on mirrors equipped with additional options

# **MODELS**

Base Model*	Dimensions	Power Requirements
ARI2-RC2.0-24.00x36.00-L7CS-30K	24"W x 36"H x 1.75"D (610mm x 914mm x 44mm)	120/240 VAC, 49W
ARI2-RC2.0-36.00x36.00-L7CS-30K	36"W x 36"H x 1.75"D (914mm x 914mm x 44mm)	120/240 VAC, 62W
ARI2-RC2.0-48.00x36.00-L7CS-30K	48"W x 36"H x 1.75"D (1219mm x 914mm x 44mm)	120/240 VAC, 73W
ARI2-RC2.0-60.00x36.00-L7CS-30K	60"W x 36"H x 1.75"D (1524mm x 914mm x 44mm)	120/240 VAC, 88W

<sup>\*</sup>Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

**DIMENSIONAL DRAWING** (Not to scale. Frost and border widths may vary depending on mirror size.)

