# Gas Cooktop, 36", LPG

Series 9 | Professional

Stainless Steel | LPG



A powerful high-heat five burner with precision control and performance. Pair with any other appliance in our Professional range.

- Your burners can deliver anything from a high 20,000 BTU heat per burner for fast boiling, to a gentle flame for simmering
- Continuous surface grates designed for pots and pans to move safely across the cooktop
- Designed to match Professional style appliances
- Made from quality materials and real stainless steel

### DIMENSIONS

| Height | 5 <sup>1</sup> / <sub>2</sub> " |
|--------|---------------------------------|
| Width  | 36 "                            |
| Depth  | 21 ″                            |

### **FEATURES & BENEFITS**

### Cooktop power

Sealed Dual Flow Burners<sup>™</sup> deliver cooktop power up to 20,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

### SPECIFICATIONS

| 20,000 BTU |
|------------|
| 12,000 BTU |
| 12,000 BTU |
| 20,000 BTU |
| 12,000 BTU |
| 12,000 BTU |
| 68,000 BTU |
|            |

| Controls                     |                             |
|------------------------------|-----------------------------|
| Metal illuminated dials      | •                           |
| Titanium coated, illuminated | •                           |
|                              |                             |
| Gas requirements             |                             |
| Fitting and pipe             | ½ NPT, min. 5%" 🛛 flex line |
| Supply Pressure (LPG)        | 11" to 14" W.C              |
|                              |                             |

| Sealed cooking surface | •     |  |
|------------------------|-------|--|
| Simmer on all burners  | 140°F |  |
| Power requirements     |       |  |

### Power requirements

Sealed Dual Flow Burners™

Performance

| Amperage         | 15A  |
|------------------|------|
| Supply frequency | 60Hz |
| Supply voltage   | 120V |

### **Product dimensions**

| Depth  | 21 ″                            |
|--------|---------------------------------|
| Height | 5 <sup>1</sup> / <sub>2</sub> " |
| Width  | 36 "                            |

### Recommended back guards and ventilation

| Downdraft        | HD36                   |
|------------------|------------------------|
| Minimum CFM      | 600                    |
| Pro hood         | HCB36-12 N / HCB36-6 N |
| Traditional hood | ES36                   |

# Warranty Parts and labor 2 years SKU 82025

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions

5

## FISHER & PAYKEL

### QUICK REFERENCE GUIDE > CDV3-365H-L

and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



Service & Warranty Booklet

✓ Installation Guide



### A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com