## **UL SPECIFICATION** \* FIXTURE SHALL BE LISTED FOR LOCATION ONLY AND LABELED AS SUCH. \* FIXTURE MUST BE MANUFACTURED IN ACCORDANCE WITH UL STANDARD 1598. PARTS SPECIFICATIONS ITEM QTY DESCRIPTION (1) SOCKET- UL LISTED/CSA CERTIFIED BASE= MEDIUM SOCKET= PORCELIN SEE LEAD WIRE FOR SOCKET WIRE SPEC. 220 [8 5/8"] LEAD WIRE- 120" FROM FRAME TOP В (1) UL LISTED/CSA CERTIFIED, AWG #18 $[4 \ 3/8]$ 105°C BLACK AND WHITE WIRE. STRIP 1/2 [12.7], SPLIT 3 [76.2]. 0 0 0 FROM TOP OF SCROLL. 110 (SEE CHART FOR COLOR). C (1) GROUND WIRE- 120" FROM FRAME TOP 220 [8 5/8"] 1/4 LAY COPPER GROUND WIRE. FROM TOP OF SCROLL. (SEE CHART FOR TINT). [3/4'']20 R&D 2020.07.31 Mark ®12.7 [Ø1/2"] INNOVATIONS LIGHTING DESIGN COPYRIGHT - 11/12/2020 ALL RIGHTS RESERVED AND MAY NOT BE DUPLICATED WITHOUT OUR WRITTEN PERMISSION 5 **DESCRIPTION ø**78 [3 1/8"] **ø**105 [4 1/8"] 855 [33 5/8"] INNOVATIONS CREATIVITY MEETS EVOLUTIONARY DESIGNO "mm" DIMENSION INDICATED IN [] DIMENSION IN [] IS FOR REF. ONLY DRAWN IN THIRD ANGLE **4LT PENDANT** TOLERANCES (EXCEPT AS NOTED) **PROJECTION** DECIMAL ANGULAR FRACTIONAL SCALE REV. NONE ±.031 ± 1/2° $\pm 1/32$ **PENDANT** .X ±.015 REVA DATE ITEM NO. DL190307-4TR(BK) 7/31/2020 .XXX ±.005