

DA 6881

30-inch downdraft ventilation hood
optional external or internal blower for maximum versatility.



- Striking design - telescopic canopy 30 (762) inches wide.
- Practical - 15-minute automatic blower run-on
- Suitable for every home - vented or recirculating
- For perfect functionality - accessories for proper venting

EAN: 4002515823965 / material number: 10595900

Construction type	
Downdraft extractor system	•
Design	
Color	Stainless steel
Edge extraction	•
Operating modes	
Recirculated mode	Convertible
OdorFree charcoal filter (order separately)	DKF18-900
Control panel	
Electronic controls	•
Light-touch controls	•
Power levels (number excl. Intensive)	3
Intensive setting	•
Run-on time 15 mins.	•
Hood in Motion	•
Filter system	
Dishwasher-safe grease filters	2
Lighting	
Light intensity in Lx	280
Color temperature in K	4,000
Safety	
Safety shut-off	•
Single-ply safety glass (ESG)	•
Technical data	
Overall hood height for vented and external in in.(mm)	41 1/2 (1,052)
Overall hood height for recirculation in in.(mm)	41 1/2 (1,052)
Canopy width in in.(mm)	30 (762)
Height of hood canopy in in.(mm)	25 1/2 (646)
Depth of hood canopy in in.(mm)	4 3/4 (120)
Net weight in lbs. (kg)	52 (23.5)
Length of electrical wire in ft (m)	4 (1.5)
Standard plug fitted	•
Total connected load in kW	0.35
Voltage in V	120
Fuse rating in A	10
Number of phases	1
Installation notes	
Vent connection at top,rear,side,bottom	•
Diameter of vent connection in in.(mm)	6 (150)
Standard accessories	
Reducer from 150 to 125 mm Ø	•

