FV-08WQ1_SpecSheet



WhisperWallTM Wall Mounted Fan

FV-08WQ1

• MORE DETAILS	• Static Pressure (in inches w.g.) 0.03
	• Air Volume (CFM) 70 (54 at 0.25" static pressure)
	• Noise (sones) 1.1
	• Power Consumption (Watts) 18 at 0.03" static pressure
	• Energy Efficiency (CFM's/Watt) 3.9
	• Speed (RPM) 660 at 0.03" static pressure
	• Current (Amps) 0.2 (0.2 at 0.25" static pressure)
	• Power Rating (V/Hz) 120/60
	• Motor Type Condenser
	• Type of Motor Bearing Sleeve
	• Thermal Fuse Protection Yes
	• Blower Wheel Type Propeller
	• Duct Diameter (inches) 8"
	• Mounting Opening (inches sq.) Use Enclosed Template
	• Grille Size (inches sq.) 10 1/8"
	• Light No
	• UL Listed for Tub/ Shower Enclosure Yes, when used with a GFCI branch circuit wire
	• Mfg in ISO 9001 Certified Facility Yes
	• Super Quiet Operation Yes
	• Energy Star Qualified Yes

- Totally Enclosed Condenser Motor Yes, for long life Rated for continuous run
- Easy Installation Yes

- Rust Proof Paint Treatment Yes, on galvanized housing
- Built-In Damper Yes, to prevent back draft
- Contemporary Grille Design Yes
- Weight 12.1 lbs

.

• • **UPC**092281137674

.....