

Project Name

Location

Prepared By



SATCO S11900

2W/LED/T5/840/BP

Notes

General

Status	Active
Watts	2
Fluorescent Equivalent	4
Volts	120V-277V
Ballast Type	Type B
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	6
Finish	Frosted
CCT (Kelvin)	4000
Temperature	Cool White
CRI	82
Lumens	150
Beam Spread	240
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	No ballast or external driver required
Operating Frequency	50/60 Hz
Dimming Type	N/A
Power Factor	0.9
Operating Temperature	-25C (-13F) to a maximum of +45C (+113F)

Physical

MOL	5.91
MOD	0.63
Weight (lb.)	0.05

Additional Information

Additional Info	Replaces F4T5/CW lamps; All glass tube
Shatter-Proof Type	PET Coated
Installation Notes	Direct wire 120-277V line voltage; Double ended wiring
Warranty	5 Year Limited - T5 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
NSF Approved	Yes - Approved

