

Project Name

Location

Prepared By



Notes

### General

Status	Active
Watts	11
Fluorescent Equivalent	25
Volts	120V-277V
Ballast Type	Type C
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	36
Finish	Frosted
CCT (Kelvin)	3500
Temperature	Neutral White
CRI	82
Lumens	1600
Beam Spread	220
Dimmable	0-10V Dimming Only
Hours Rated	50000
Lamp Type	Linear
Technology	LED

### Electrical

Ballasting Requirements	Ballast replaced with external driver
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

### Physical

MOL	36
MOD	1
Weight (lb.)	0.34

### Additional Information

Additional Info	Not for emergency lighting
Tube Guard Use	Approved for use with tube guards
Warranty	5 Year Limited - T8 LED Bulbs

### Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLE306JZGWQU
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)

