

Project Name

Location

Prepared By



## SATCO S8537

9WPLV/LED/835/BP/2P

### Notes

### General

Status	Active
Watts	9
Fluorescent Equivalent	See Notes
Volts	120V-277V
Ballast Type	Type B
Shape	PL
Base	2-Pin
ANSI Base	G24d
Finish	Frosted
CCT (Kelvin)	3500
Temperature	Neutral White
CRI	82
Lumens	950
Beam Spread	120
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	PL
Burning Position	Vertical Operation
Technology	LED

### Electrical

Ballasting Requirements	Ballast By-pass; Direct wire voltage range 100-277V
Operating Frequency	50/60 Hz
Dimming Type	N/A
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

### Physical

MOL	4.69
MOD	1.91

### Additional Information

Additional Info	In G24d (2-pin) sockets replaces 18 and 26 watt CFLs; In G24q (4-pin) sockets replaces 13; 18; and 26 watt CFLs
Installation Notes	2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.
Warranty	5 Year Limited - 10 hr per day

### Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
SDS Sheet	LED_Lamp

