TOTO_®

MW6342034CEFG

Supreme[®] II / WASHLET[®]+ C100 One-Piece Toilet - 1.28 GPF

FEATURES

- Concealed supply connection for seamless installation
- High-efficiency Tornado Flush[®] (1.28GPF/4.8LPF)
- CeFiONtect[®] glaze prevents debris from sticking to ceramic surfaces for easy cleaning
- Universal Height
- Elongated front bowl
- Decorative one-piece design with high-profile tank
- Chrome trip lever
- 12" Rough-in, less supply
- See Spec sheet SW2034T20 for Washlet features

MODELS

• CST634CEFGT20 - With CeFiONtect glaze

REQUIRED WASHLET+

 SW2034T20 WASHLET®+ C100 Fits TOTO WASHLET+ toilet bowl models only

COLORS/FINISHES

• Standard #01 Cotton

PRODUCT SPECIFICATION

The one-piece high-efficiency Tornado Flush toilet shall be 1.28GPF/4.8LPF. Universal Height Toilet with CeFiONtect glaze finish. Toilet shall have high-profile tank, elongated front bowl and chrome trip lever. Toilet shall be **TOTO Model CST634CEFGT20#01**.

See TOTO Specification sheet **SW2034T20** for details on required Washlet.



😵 CeFiONtect wasમၬင်ဴာ.+ ခ္ဓာ Tornado Flush

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), EPA WaterSense, State of Massachusetts , City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- ADA compliant (when installed with trip lever located on the approach side)



MS6342034CEFG

Supreme[®] II / WASHLET[®]+ C100 One-Piece Toilet - 1.28 GPF

SPECIFICATIONS

- 1.28 GPF/4.8LPF Water Use
- Flush System .

Tornado Flush®

- Min. Water Pressure 8 psi (flowing) 7-1/8" x 9-1/8" Water Surface
- Trap Diameter 2-1/8"
- Rough-in
- Trap Seal 2-1/8"
- Warranty One Year Limited Warranty


12"

- Material
- Vitreous china Shipping Weight CST634CEFGT20 104lbs. SW2034T20 16.0lbs.
- Shipping Dimensions CST634CEFGT20 29-1/2" L x 18"W x 19-1/4" H¹ x 27-1/8" H² SW2034T20 23 1/2"X 20 1/2" X 9"
- See Spec sheet SW2034T20 for Washlet details FINISHED WALL


INSTALLATION NOTES

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.



These dimensions and specifications are subject to change without notice