








Shown with optional duct cover



FRONT



SIDE



WALL



MODEL

Matte BlackDAP-M90AMBXMatte WhiteDAP-M90AMWXSize90cm (35-3/8")

BLOWER PERFORMANCE

 Internal Blower (CBI-290C)*
 200-290 CFM, 1.4-3 sones

 Internal Blower (CBI-600A)*
 240-600 CFM, 1.8-6 sones

 In-Line Blower (PBN-1000A)*
 500-1,000 CFM, sones NA

 External Blower (CBE-1000)*
 500-1,000 CFM, sones NA

FEATURES

Controls Capacitive Touch

Speed Levels3Auto Delay-OffYesCleanAir Function**YesLightingLED, 5W x2

Tri-Level Lighting Yes

Filters Aluminum Mesh x2

Recirculating*** Yes

ADA Compliant Yes, with remote option

DUCT SPECIFICATIONS

Vertical Single Internal Blower 6" Round

Vertical In-Line/External Blower 10" to 8" Round****

Horizontal Single Internal Blower 6" Round

Horizontal In-Line/External Blower 10" to 8" Round****

AC POWER

 Hood w/ CBI-290C
 120V, 60Hz, Max. 1A

 Hood w/ CBI-600A
 120V, 60Hz, Max. 3A

 Hood w/ PBN-1000A
 120V, 60Hz, Max. 5.4A

 Hood w/ CBE-1000
 120V, 60Hz, Max. 6.6A

OPTIONAL ACCESSORIES

Recirculating Kit ZRC-00AP

Remote Control 14000010

Duct Cover - Matte Black Z1C-00MEMB

Duct Cover - Stainless Steel Z1C-00MESS

Make-Up Air Kit MUA006A (600 CFM)

MUA008A (1,000 CFM)

MOUNTING HEIGHT RANGE† 22" - 34"

WARRANTY 2 year parts, 1 year labor

HOOD HEIGHT CALCULATOR - With Optional Duct Cover

CEILING HEIGHT	8'	8.5'	9,	9.5'	10'	10.5'	11'	12'
MOUNTING HEIGHT†	NA	NA	22" - 22"	22" - 28"	24" - 34"	30" - 34"	NA	NA

^{*}Blower sold separately.

^{****10&}quot; round duct connects to external and in-line blower. Must transition from 10" to 8" before duct passes through ceiling. A 10" to 8" adapter is included with external and in-line blowers. †Mounting height refers to distance between top of a 36" tall cooking surface and bottom of hood.



^{**}CleanAir turns your hood on once every four hours for 10 minutes on speed one.

^{***}Not compatible with optional duct cover.